



TALK-SPEAKER RANGE

The Talk-Speaker range consists of 3 Remote Speaker Microphone solutions and a hub that allow users to communicate easily and quickly with one another.

Delivering high sound power, the speakers in the RSM units enable communication across different operational environments using 4G mobile networks and 450 MHz point-to-point radio links.

- COMPLETE RANGE**
Comprising 4 products with diverse functionalities.
- TAILORED TO NEEDS**
Comprehensive and modular products that address all field requirements.
- DESIGNED WITH USERS IN MIND**
Products developed based on user feedback and preferences.

Supported by



GOUVERNEMENT

*Liberté
Égalité
Fraternité*

BRIDGING TECHNOLOGY



Provides DMR radio coverage across the entire operational intervention field, either as a redundancy or as a complement to the LTE network.

ERGONOMICS



This fully configurable solution reduces the number of devices needed by operational teams while ensuring ease of use. The entire design has been crafted to guarantee optimal accessibility in the field.

MCTS APPLICATION



Through the MCTS (Mission Critical Talk-Speaker) application, the system is fully configurable, offering a completely integrated multi-conferencing solution.

NETWORK COMPATIBILITY



Supports 4G/5G/6G networks as well as legacy networks: TETRAPOLE, ACROPOL, ANTARES, ADAGIO, Iris, Opera, SERVIR, Rubis et Corail NG, ARCAP, RORCAL, RENABEC, Airewave, ASTRID, C2000, RAKEL, VIRVE, P25

TECHNICAL FEATURES

MICRO-HANDSET SOLUTIONS :

- Talk-Speaker : Basic functionalities of the range.
- Talk-Speaker **Évo** : Includes all Talk-Speaker functionalities **plus a customizable rotary switch for easy conference selection.**
- Talk-Speaker Direct : **All Talk-Speaker Évo functionalities** plus integrated DMR module and bridging features 1.0 and 2.0.

	Models	Talk Speaker	Talk Speaker-Évo	Talk Speaker-Direct
	Weight	250g	260g	300g
General Features	Fixation : Rotating clamp 360°	✓	✓	✓
	Battery 3000 mAh	✓	✓	✓
	Replaceable battery	✓	✓	✓
	Speaker > 110dB	✓	✓	✓
	High-performance microphone	✓	✓	✓
Connectivity	Smartphone : Wired or Bluetooth	✓	✓	✓
	Headset: Wired or Bluetooth	✓	✓	✓
Features	Multiple Push-to-Talk	✓	✓	✓
	LTE Alarm	✓	✓	✓
	Gateway function 1.0	<i>Via Talk-Speaker Hub (option)</i>		✓
	Configurable rotator	-	✓	✓
	Gateway function 2.0	-	-	✓
	Integrated DMR	-	-	✓
	DMR Alarm	-	-	✓
Ports / Compatibility	Ports	1 dedicated USB-C for Voice-Data / 1 USB-C for charging		
	Compatibility	MCTS / ToM&ToTR / Other MCPTT (upon request)		
Options	Bluetooth remote alternates	✓	✓	✓
	2 Alternates	✓	✓	✓
	Connection cable input/output options:	Choose from: USB-C to USB-C / USB-C to 3.5mm Jack or USB-C to USB-C and 3.5mm Jack		
Environment	Target standards	IP68 / MIL-STAND-810		

TALK-SPEAKER HUB :

The Talk-Speaker Hub connects all your equipment and provides bridging capabilities, enabling interconnection between radio networks (e.g., TETRA) and LTE.

It can be used with the Talk-Speaker or Talk-Speaker Évo, allowing direct control of the device from your chest rig.

	Specifications	Talk-Speaker Hub
General Features	Weight	150g
	Battery	2000 mAh
	Mounting	Smartphone Mounting
Connectivity	Equipments	Wired
Features	Gateway	Gateway Version 1.0
	LTE Alarm	Via the MCTS application
	Push to Talk	Via the Talk-Speaker
Ports and compatibility	Ports	3 dedicated USB-C / 1 USB-C Data
	Compatibility	1 DMO, MCTS, ToM&ToTR, All MCPTT
Option	Cable Options	DMO wiring option



Supported by

